UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

	APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
	10/528,365	07/19/2005	Lionel Tarassenko	117-537	5031
	23117 7590 05/15/2007 NIXON & VANDERHYE, PC		7	EXAMINER	
901 NORTH GLEBE ROAD, 11TH FLOO		LEBE ROAD, 11TH F	OR	NAQI, SHARICK	
	ARLINGTON,	ARLINGTON, VA 22203	•	ART UNIT	PAPER NUMBER
				3736	
				<u></u>	
				MAIL DATE	DELIVERY MODE
				05/15/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

•		Application No.	Applicant(s)				
		10/528,365	TARASSENKO ET AL.				
	Office Action Summary	Examiner	Art Unit				
		Sharick Naqi	3736				
Period fo	- The MAILING DATE of this communication app r Reply	ears on the cover sheet with the c	orrespondence address				
WHIC - Exten after \$ - If NO - Failure Any re	DRTENED STATUTORY PERIOD FOR REPLY HEVER IS LONGER, FROM THE MAILING DA sions of time may be available under the provisions of 37 CFR 1.13 SIX (6) MONTHS from the mailing date of this communication. period for reply is specified above, the maximum statutory period w e to reply within the set or extended period for reply will, by statute, eply received by the Office later than three months after the mailing d patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tin vill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).				
Status							
1) 🖂	Responsive to communication(s) filed on 03 M	arch 2005.					
·		action is non-final.					
3)	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is						
	closed in accordance with the practice under E	x parte Quayle, 1935 C.D. 11, 45	53 O.G. 213.				
Dispositio	on of Claims						
4) 🖂	☑ Claim(s) <u>1-35</u> is/are pending in the application.						
	4a) Of the above claim(s) is/are withdrawn from consideration.						
5)	Claim(s) is/are allowed.						
6)⊠							
·	Claim(s) is/are objected to.						
8)	Claim(s) are subject to restriction and/or	r election requirement.					
Application	on Papers						
9)[] 7	The specification is objected to by the Examine	r.					
10)⊠ 7)⊠ The drawing(s) filed on is/are: a)⊠ accepted or b)⊡ objected to by the Examiner.						
•	Applicant may not request that any objection to the	drawing(s) be held in abeyance. See	∍ 37 CFR 1.85(a).				
	Replacement drawing sheet(s) including the correcti		, ,				
11)1	The oath or declaration is objected to by the Ex	aminer. Note the attached Office	Action or form PTO-152.				
Priority u	nder 35 U.S.C. § 119						
a)[∑	2)⊠ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a)⊠ All b)□ Some * c)□ None of:						
	 Certified copies of the priority documents Certified copies of the priority documents 		an Na				
	2. Certified copies of the priority documents3. Copies of the certified copies of the prior						
	application from the International Bureau		on the National Stage				
* S	ee the attached detailed Office action for a list	* **	ed.				
		•					
Attachment	· ·						
	e of References Cited (PTO-892)	4) Interview Summary	(PTO-413)				
2) Notice	of Draftsperson's Patent Drawing Review (PTO-948)	Paper No(s)/Mail Da	ate				
	nation Disclosure Statement(s) (PTO/SB/08) No(s)/Mail Date <u>3/18/2005, 1/03/2006</u> .	5) Notice of Informal P 6) Other:	atent Application				

DETAILED ACTION

Priority

Acknowledgment is made of applicant's claim for foreign priority under 35 U.S.C. 119(a)-(d).

Claim Objections

Claims 8, 9 and 28 are objected to because of the following informalities:

In regards to claim 8, examiner suggests that proper alternate form be used and "cell phone/pda" be corrected to "cell phone or pda."

In regards to claim 9, examiner suggests that proper alternate form be used and "cell phone/pda" be corrected to "cell phone or pda."

In regards to claim 28, "the a wireless transmitter", on page 9, line 15, is a typographical error. Examiner suggests that it be corrected to "a wireless transmitter" or "the wireless transmitter."

Appropriate correction is required.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

⁽b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

⁽e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the

Art Unit: 3736

applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claims 1-5, 8-16 and 18-30 are rejected under 35 U.S.C. 102(b) as being anticipated by Walker et al. USPN 6,302,844.

1. A telemedicine system comprising a patient-based physiological data acquisition and transmittal device connectable via a wireless network to transmit physiological data to a remote server, wherein the patient-based measurement and data transmittal device comprises:

an electronic physiological data acquisition unit for measuring a physiological parameter of a patient to acquire and output data representing the parameter; (fig. 1, column 4, lines 7-67, column 5, lines 1-44)

a wireless transmitter which upon receiving the output data from the data acquisition unit automatically transmits the output data via the wireless network to the remote server. (fig. 1, column 4, lines 7-67, column 5, lines 1-44)

2. A telemedicine system according to claim 1 wherein the wireless transmitter is adapted to receive automatically the output data from the physiological data acquisition unit on data acquisition thereby, and thereupon automatically to transmit the output data immediately in real time to the remote server. (fig. 1, column 4, lines 7-67, column 5, lines 1-44)

3. A telemedicine system according to claim 1 wherein the wireless transmitter is adapted to establish a connection to the wireless network automatically when it is switched on and to maintain the connection while switched on. (fig. 1, column 4, lines 7-67, column 5, lines 1-44)

- 4. A telemedicine system according to claim 1, wherein the wireless network is a packet-switched network. (fig. 1, column 4, lines 7-67, column 5, lines 1-44, column 6, lines 3-15)
- 5. A telemedicine system according to claim 4 wherein the wireless network is a public network. (fig. 1, column 4, lines 7-67, column 5, lines 1-44, column 6, lines 3-15)
- 8. A telemedicine system according to claim 1 wherein the wireless transmitter is a cellular telephone/pda. (fig. 1, column 4, lines 7-67, column 5, lines 1-44, column 6, lines 3-15)
- 9. A telemedicine system according to claim 8 wherein a software application is provided on the cellular telephone/pda to interface with the physiological data acquisition unit and to control data transmission to the remote server. (fig. 1, column 4, lines 7-67, column 5, lines 1-44, column 6, lines 3-15)
- 10. A telemedicine system according to claim 1 wherein the patient-based

measurement and data transmittal device is adapted to check the acquired data for compliance with preset conditions. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15)

- 11. A telemedicine system according to claim 10 wherein the preset conditions relate to the quality or completeness of the data or the condition of the patient. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15)
- 12. A telemedicine system according to claim 1 wherein the patient-based measurement and data transmittal device comprises a display for displaying the data to the patient. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15)
- 13. A telemedicine system according to claim 1 wherein the patient-based measurement and data transmittal device stores the data if a network connection is unavailable and automatically retransmits it later when a network connection is available. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15)
- 14. A telemedicine system according to claim 1 wherein the remote server processes the data to check the condition of the patient and responds with a message via the wireless network. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67,

column 6, lines 1-15, column 8, lines 5-39)

15. A telemedicine system according to claim 1 wherein the remote server formats the data for delivery and display to a clinician. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59)

- 16. A telemedicine system according to claim 1 wherein the remote server comprises a data analyser for identifying trends in the data and a message generator for generating messages to be output to at least one of the patient and a clinician. (fig. 1, column 4, lines 7-67, column 5, lines 1-44, column 7, lines 45-63)
- 18. A telemedicine system according to claim 1 wherein the physiological data acquisition unit is one of: an electronic flow meter for recording Peak Expiratory Flowrate, an electronic blood glucose meter, a blood pressure monitor, and a heart rate monitor. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59)
- 19. A telemedicine system according to claim 1 wherein the physiological data acquisition unit and wireless transmitter are integrated as a single device. (fig. 1, column 4, lines 7-67, column 5, lines 1-44)

Art Unit: 3736

20. A telemedicine system according to claim 1 wherein the data sent from the wireless transmitter is time stamped with reference to a secure clock. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59, column 21, lines 20-25)

- 21. A telemedicine system according to claim 20 wherein the secure clock is provided in the patient-based physiological data acquisition and transmittal device. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59, column 21, lines 20-25)
- 22. A telemedicine system according to claim 1 wherein a secure data store is provided in the patient-based physiological data acquisition and transmittal device. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59, column 21, lines 20-25)
- 23. A telemedicine system according to claim 1 wherein the data sent from the wireless transmitter is digitally signed. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59)
- 24. A telemedicine system according to claim 1 wherein the data sent from the wireless transmitter comprises the location of the wireless transmitter. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-45, column 8, lines 5-39,

column 19, lines 55-59)

25. A telemedicine system according to claim 24 wherein information is sent from the server to the patient-based physiological data acquisition and transmittal device for display thereon and is adapted depending on the location of the wireless transmitter. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59)

- 26. A telemedicine system according to claim 1 wherein information is sent from the server to the patient-based physiological data acquisition and transmittal device for display thereon to initiate interaction with the patient and is adapted depending on the value of the physiological parameter measured by the electronic physiological data acquisition unit. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59)
- 27. A telemedicine system according to claim 1 wherein information is sent from the server to the patient-based physiological data acquisition and transmittal device, and wherein in dependence upon said physiological parameter measurement and transmission to the server said information comprises a prescription for medication. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59)

28. A telemedicine system according to claim 1 wherein the electronic physiological data acquisition unit is connectable to the a wireless transmitter by a connection comprising a data head including an interface. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59)

- 29. A telemedicine system according to claim 28 wherein the data head comprises a secure clock for time stamping the data. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59, column 21, lines 20-25)
- 30. A telemedicine system according to claim 28 wherein the data head comprises a secure memory for storing the data. (fig. 1, column 4, lines 7-67, column 5, lines 1-44 and lines 58-67, column 6, lines 1-15, column 8, lines 5-39, column 19, lines 55-59, column 21, lines 20-25)

Claims 1-5, 8-16 and 18-35 are rejected under 35 U.S.C. 102(b) as being anticipated by Blants et al. USPN 6,231,519.

1. A telemedicine system comprising a patient-based physiological data acquisition and transmittal device connectable via a wireless network to transmit physiological data to a remote server, wherein the patient-based measurement and data transmittal device comprises:

Page 10

an electronic physiological data acquisition unit for measuring a physiological parameter of a patient to acquire and output data representing the parameter; (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

a wireless transmitter which upon receiving the output data from the data acquisition unit automatically transmits the output data via the wireless network to the remote server. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

- 2. A telemedicine system according to claim 1 wherein the wireless transmitter is adapted to receive automatically the output data from the physiological data acquisition unit on data acquisition thereby, and thereupon automatically to transmit the output data immediately in real time to the remote server. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 3. A telemedicine system according to claim 1 wherein the wireless transmitter is adapted to establish a connection to the wireless network automatically when it is switched on and to maintain the connection while switched on. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 4. A telemedicine system according to claim 1, wherein the wireless network is a packet-switched network. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

Page 11

5. A telemedicine system according to claim 4 wherein the wireless network is a public network. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

- 8. A telemedicine system according to claim 1 wherein the wireless transmitter is a cellular telephone/pda. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 9. A telemedicine system according to claim 8 wherein a software application is provided on the cellular telephone/pda to interface with the physiological data acquisition unit and to control data transmission to the remote server. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 10. A telemedicine system according to claim 1 wherein the patient-based measurement and data transmittal device is adapted to check the acquired data for compliance with preset conditions. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 11. A telemedicine system according to claim 10 wherein the preset conditions relate to the quality or completeness of the data or the condition of the patient. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

Art Unit: 3736

- 12. A telemedicine system according to claim 1 wherein the patient-based measurement and data transmittal device comprises a display for displaying the data to the patient. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 13. A telemedicine system according to claim 1 wherein the patient-based measurement and data transmittal device stores the data if a network connection is unavailable and automatically retransmits it later when a network connection is available. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 14. A telemedicine system according to claim 1 wherein the remote server processes the data to check the condition of the patient and responds with a message via the wireless network. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 15. A telemedicine system according to claim 1 wherein the remote server formats the data for delivery and display to a clinician. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 16. A telemedicine system according to claim 1 wherein the remote server comprises a data analyser for identifying trends in the data and a message generator for generating messages to be output to at least one of the patient and a clinician. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

- 18. A telemedicine system according to claim 1 wherein the physiological data acquisition unit is one of: an electronic flow meter for recording Peak Expiratory Flowrate, an electronic blood glucose meter, a blood pressure monitor, and a heart rate monitor. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 19. A telemedicine system according to claim 1 wherein the physiological data acquisition unit and wireless transmitter are integrated as a single device. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 20. A telemedicine system according to claim 1 wherein the data sent from the wireless transmitter is time stamped with reference to a secure clock. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 21. A telemedicine system according to claim 20 wherein the secure clock is provided in the patient-based physiological data acquisition and transmittal device. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 22. A telemedicine system according to claim 1 wherein a secure data store is provided in the patient-based physiological data acquisition and transmittal device. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

23. A telemedicine system according to claim 1 wherein the data sent from the wireless transmitter is digitally signed. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

- 24. A telemedicine system according to claim 1 wherein the data sent from the wireless transmitter comprises the location of the wireless transmitter. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 25. A telemedicine system according to claim 24 wherein information is sent from the server to the patient-based physiological data acquisition and transmittal device for display thereon and is adapted depending on the location of the wireless transmitter. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 26. A telemedicine system according to claim 1 wherein information is sent from the server to the patient-based physiological data acquisition and transmittal device for display thereon to initiate interaction with the patient and is adapted depending on the value of the physiological parameter measured by the electronic physiological data acquisition unit. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 27. A telemedicine system according to claim 1 wherein information is sent from the server to the patient-based physiological data acquisition and transmittal device, and wherein in dependence upon said physiological parameter measurement and

transmission to the server said information comprises a prescription for medication. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

- 28. A telemedicine system according to claim 1 wherein the electronic physiological data acquisition unit is connectable to the a wireless transmitter by a connection comprising a data head including an interface. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 29. A telemedicine system according to claim 28 wherein the data head comprises a secure clock for time stamping the data. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 30. A telemedicine system according to claim 28 wherein the data head comprises a secure memory for storing the data. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 31. A telemedicine system which incorporates handset delivery of advice relating to changes in medication necessary to control a respiratory condition including asthma. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 32. A telemedicine system according to claim 31 wherein the handset comprises a graphical device indicating the state of an asthmatic condition relative to an alert level.

(column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

- 33. A telemedicine system according to claim 31 wherein the medication advice is based on readings analysed by software at the server and/or handset. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 34. A telemedicine system which incorporates handset delivery of geographically local information relevant to the patient condition from a central server, such information being derived from knowledge of the geographic location of the wireless handset and being adapted based on measurement of the patient condition by the telemedicine system. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)
- 35. A telemedicine system according to claim 34 wherein said local information comprises local air quality information and weather conditions relevant to patients with respiratory diseases. (column 2, lines 52-65, column 4, lines 1-67, column 5, lines 1-67)

Claims 1-5, 8-13, 18-23 and 28-30 are rejected under 35 U.S.C. 102(e) as being anticipated by Schulze et al. USPN 6,443,890.

1. A telemedicine system comprising a patient-based physiological data acquisition and transmittal device connectable via a wireless network to transmit physiological data to a remote server, wherein the patient-based measurement and data transmittal device comprises:

an electronic physiological data acquisition unit for measuring a physiological parameter of a patient to acquire and output data representing the parameter; (column 2, lines 15-61)

a wireless transmitter which upon receiving the output data from the data acquisition unit automatically transmits the output data via the wireless network to the remote server. (column 2, lines 15-61)

- 2. A telemedicine system according to claim 1 wherein the wireless transmitter is adapted to receive automatically the output data from the physiological data acquisition unit on data acquisition thereby, and thereupon automatically to transmit the output data immediately in real time to the remote server. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)
- 3. A telemedicine system according to claim 1 wherein the wireless transmitter is adapted to establish a connection to the wireless network automatically when it is switched on and to maintain the connection while switched on. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)
- 4. A telemedicine system according to claim 1, wherein the wireless network is a packet-switched network. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)

5. A telemedicine system according to claim 4 wherein the wireless network is a public network. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)

- 8. A telemedicine system according to claim 1 wherein the wireless transmitter is a cellular telephone/pda. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)
- 9. A telemedicine system according to claim 8 wherein a software application is provided on the cellular telephone/pda to interface with the physiological data acquisition unit and to control data transmission to the remote server. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)
- 10. A telemedicine system according to claim 1 wherein the patient-based measurement and data transmittal device is adapted to check the acquired data for compliance with preset conditions. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)
- 11. A telemedicine system according to claim 10 wherein the preset conditions relate to the quality or completeness of the data or the condition of the patient. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)

12. A telemedicine system according to claim 1 wherein the patient-based measurement and data transmittal device comprises a display for displaying the data to the patient. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)

- 13. A telemedicine system according to claim 1 wherein the patient-based measurement and data transmittal device stores the data if a network connection is unavailable and automatically retransmits it later when a network connection is available. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)
- 18. A telemedicine system according to claim 1 wherein the physiological data acquisition unit is one of: an electronic flow meter for recording Peak Expiratory Flowrate, an electronic blood glucose meter, a blood pressure monitor, and a heart rate monitor. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)
- 19. A telemedicine system according to claim 1 wherein the physiological data acquisition unit and wireless transmitter are integrated as a single device. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67)
- 20. A telemedicine system according to claim 1 wherein the data sent from the wireless transmitter is time stamped with reference to a secure clock. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67, column 5, lines 25-60)

21. A telemedicine system according to claim 20 wherein the secure clock is provided in the patient-based physiological data acquisition and transmittal device. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67, column 5, lines 25-60)

- 22. A telemedicine system according to claim 1 wherein a secure data store is provided in the patient-based physiological data acquisition and transmittal device. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67, column 5, lines 25-60)
- 23. A telemedicine system according to claim 1 wherein the data sent from the wireless transmitter is digitally signed. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67, column 5, lines 25-60)
- 28. A telemedicine system according to claim 1 wherein the electronic physiological data acquisition unit is connectable to the a wireless transmitter by a connection comprising a data head including an interface. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67, column 5, lines 25-60)
- 29. A telemedicine system according to claim 28 wherein the data head comprises a secure clock for time stamping the data. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67, column 5, lines 25-60)

30. A telemedicine system according to claim 28 wherein the data head comprises a secure memory for storing the data. (column 2, lines 15-61, column 3, lines 1-59, column 4, lines 1-67, column 5, lines 25-60)

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

The factual inquiries set forth in *Graham* v. *John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

- 1. Determining the scope and contents of the prior art.
- 2. Ascertaining the differences between the prior art and the claims at issue.
- 3. Resolving the level of ordinary skill in the pertinent art.
- 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

Claim 6 is rejected under 35 U.S.C. 103(a) as being unpatentable over by Schulze et al. USPN 6,443,890 as applied to claim 5 above, and further in view of Haller et al. US Patent Pub. No. 2002/0052539.

Schulze teaches in column 5, lines 25-32 and column 7, lines 10-29, that the CDMA wireless protocol is used in the device but other wireless networks will be just as suitable for use in the device. Schulze does not disclose that the wireless network is the

General Packet Radio Service (GPRS) network. However, Haller et al., a reference in an analogous art, discloses, in paragraphs 0115-0141, the use of a GPRS network in an emergency medical information communication system. It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the wireless network of Schulze et al. with Haller et al.'s GPRS network since Haller et al. teaches, in paragraphs 0115-0141, the interchangeability of different wireless networks, including CDMA and GPRS.

Claim 7 is rejected under 35 U.S.C. 103(a) as being unpatentable over by Schulze et al. USPN 6,443,890 as applied to claim 1 above, and further in view of Haller et al. US Patent Pub. No. 2002/0052539.

Schulze teaches in column 5, lines 25-32 and column 7, lines 10-29, that the CDMA wireless protocol is used in the device but other wireless networks will be just as suitable for use in the device. Schulze does not disclose that the wireless network is the 3G, PDC-P or EDGE network. However, Haller et al., a reference in an analogous art, discloses, in paragraphs 0115-0141, the use of a 3G network in an emergency medical information communication system. It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the wireless network of Schulze et al. with Haller et al.'s 3G network since Haller et al. teaches, in paragraphs 0115-0141, the interchangeability of different wireless networks, including CDMA and 3G.

Art Unit: 3736

Claim 17 is rejected under 35 U.S.C. 103(a) as being unpatentable over by Walker et al. USPN 6,302,844. as applied to claim 16 above, and further in view of Baker, Jr. et al. USPN 5,853,364.

Walker teaches, in column 7, lines 45-63, that the remote server analyzes the received signals to determine whether the pattern or data aberration is pathological. Walker does not disclose that the data analyzer comprises a Kalman smoother for smoothing the data. Baker, Jr. et al., a reference in an analogous art, discloses, in column 4, lines 4-25, the use of a Kalman filter to reduce noise energy in a system for measuring physiological parameters. It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the data analyzer of Walker et al. with Baker, Jr. et al.'s Kalman filter since Baker Jr. et al. teaches in column 4, lines 4-25 and column 9, lines 58-60, that the Kalman filter optimally filters noise from physiological measurements and further teaches, in column 11, lines 22-36, that the Kalman filter improves accuracy of the results.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Sharick Naqi whose telephone number is 571-272-3041. The examiner can normally be reached on 8:30 am - 5:00 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Max Hindenburg can be reached on 571-272-4726. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 3736

Page 24

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

.SN May 4, 2007 Michael Astorino